

(12) **United States Patent**
Lau et al.

(10) **Patent No.:** **US 9,596,579 B2**
(45) **Date of Patent:** ***Mar. 14, 2017**

(54) **METHOD AND SYSTEM FOR ENHANCED MESSAGING**

(71) Applicant: **IpVenture, Inc.**, Los Altos, CA (US)

(72) Inventors: **Chung Lau**, Sunnyvale, CA (US); **C. Douglass Thomas**, Saratoga, CA (US)

(73) Assignee: **IpVenture, Inc.**, Los Altos, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/272,559**

(22) Filed: **Sep. 22, 2016**

(65) **Prior Publication Data**
US 2017/0013426 A1 Jan. 12, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/727,798, filed on Jun. 1, 2015, now Pat. No. 9,456,350, which is a (Continued)

(51) **Int. Cl.**
H04W 4/12 (2009.01)
H04W 4/02 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04W 4/12** (2013.01); **H04L 12/58** (2013.01); **H04L 51/38** (2013.01); **H04W 4/02** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04L 63/08; H04W 64/00; H04W 4/02; H04W 12/06; G06Q 10/107
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

3,975,941 A 8/1976 Smith
4,719,920 A 1/1988 Alt et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 874 529 A2 10/1998
EP 1 037 447 A2 9/2000
(Continued)


OTHER PUBLICATIONS

Office Action for U.S. Appl. No. 10/397,474, dated Aug. 23, 2006.
(Continued)

Primary Examiner — Kashif Siddiqui

(57) **ABSTRACT**
Techniques for acquiring, sending, receiving or using status information from a remote location over a network are disclosed. The status information is transmitted over the network between or among electronic devices. The status information can be provided by one or more sensors associated with the electronic device that is transmitting the status information. The status information can be transmitted with messages so as to enhance the messages. The electronic devices include at least computing devices, such as personal computers, personal digital assistants, pagers, and mobile telephones.

53 Claims, 7 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/802,594, filed on Mar. 13, 2013, now Pat. No. 9,049,571, which is a continuation of application No. 13/459,025, filed on Apr. 27, 2012, now Pat. No. 8,447,822, which is a continuation of application No. 13/113,972, filed on May 23, 2011, now Pat. No. 8,176,135, which is a continuation of application No. 12/214,434, filed on Jun. 19, 2008, now Pat. No. 7,953,809, which is a continuation of application No. 10/397,474, filed on Mar. 26, 2003, now Pat. No. 7,403,972.

- (60) Provisional application No. 60/444,198, filed on Jan. 30, 2003, provisional application No. 60/418,491, filed on Oct. 15, 2002, provisional application No. 60/404,645, filed on Aug. 19, 2002, provisional application No. 60/375,998, filed on Apr. 24, 2002.

- (51) **Int. Cl.**
H04L 12/58 (2006.01)
H04W 4/18 (2009.01)
H04W 12/08 (2009.01)
- (52) **U.S. Cl.**
 CPC *H04W 4/027* (2013.01); *H04W 4/185* (2013.01); *H04W 12/08* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,115,223 A 5/1992 Moody
 5,337,579 A 8/1994 Saia, III et al.
 5,347,274 A 9/1994 Hassett
 5,353,034 A 10/1994 Sato et al.
 5,389,934 A 2/1995 Kass
 5,394,333 A 2/1995 Kao
 5,400,020 A 3/1995 Jones et al.
 5,422,816 A 6/1995 Sprague et al.
 5,461,365 A 10/1995 Schlager et al.
 5,470,233 A 11/1995 Fruchterman et al.
 5,491,486 A 2/1996 Welles, II et al.
 5,512,902 A 4/1996 Guthrie et al.
 5,515,858 A 5/1996 Myllymaki
 5,528,247 A 6/1996 Nonami
 5,528,518 A 6/1996 Bradshaw et al.
 5,532,690 A 7/1996 Hertel
 5,539,748 A 7/1996 Raith
 5,541,845 A 7/1996 Klein
 5,543,789 A 8/1996 Behr et al.
 5,550,551 A 8/1996 Alesio
 5,563,606 A 10/1996 Wang
 5,568,119 A 10/1996 Schipper et al.
 5,570,412 A 10/1996 LeBlanc
 5,576,716 A 11/1996 Sadler
 5,592,173 A 1/1997 Lau et al.
 5,598,460 A 1/1997 Tendler
 5,604,708 A 2/1997 Helms et al.
 5,623,260 A 4/1997 Jones
 5,623,418 A 4/1997 Rostoker
 5,627,517 A 5/1997 Theimer et al.
 5,629,678 A 5/1997 Gargano et al.
 5,633,874 A 5/1997 Diachina et al.
 5,650,770 A 7/1997 Schlager et al.
 5,652,570 A 7/1997 Lepkofker
 5,673,692 A 10/1997 Schulze et al.
 5,686,888 A 11/1997 Welles, II et al.
 5,710,551 A 1/1998 Ridgeway
 5,712,619 A 1/1998 Simkin
 5,731,757 A 3/1998 Layson, Jr.
 5,731,788 A 3/1998 Reeds
 5,742,233 A 4/1998 Hoffman et al.
 5,751,245 A 5/1998 Janky et al.
 5,771,001 A 6/1998 Cobb

5,771,455 A 6/1998 Kennedy, III et al.
 5,774,876 A 6/1998 Woolley et al.
 5,786,789 A 7/1998 Janky
 5,797,091 A 8/1998 Clise et al.
 5,806,018 A 9/1998 Smith et al.
 5,808,565 A 9/1998 Matta et al.
 RE35,920 E 10/1998 Sorden et al.
 5,825,283 A 10/1998 Camhi
 5,826,195 A 10/1998 Westerlage et al.
 5,835,907 A 11/1998 Newman
 5,841,352 A 11/1998 Prakash
 5,844,862 A 12/1998 Cocatre-Zilgien
 5,850,196 A 12/1998 Mowers
 5,861,841 A 1/1999 Gildea et al.
 5,883,594 A 3/1999 Lau
 5,889,770 A 3/1999 Jokiahio et al.
 5,892,454 A 4/1999 Schipper et al.
 5,894,266 A 4/1999 Wood, Jr. et al.
 5,902,347 A 5/1999 Backman et al.
 5,905,461 A 5/1999 Neher
 5,910,799 A 6/1999 Carpenter et al.
 5,913,078 A 6/1999 Kimura et al.
 5,917,433 A 6/1999 Keillor et al.
 5,918,180 A 6/1999 Dimino
 5,928,309 A 7/1999 Korver et al.
 5,938,721 A 8/1999 Dussell et al.
 5,948,040 A 9/1999 DeLorme et al.
 5,948,043 A 9/1999 Mathis
 5,950,125 A 9/1999 Buhrmann et al.
 5,959,575 A 9/1999 Abbott
 5,959,577 A 9/1999 Fan et al.
 5,963,130 A 10/1999 Schlager et al.
 5,970,388 A 10/1999 Will
 5,982,285 A 11/1999 Bueche et al.
 5,982,807 A 11/1999 Snell
 5,983,108 A 11/1999 Kennedy, III et al.
 5,983,158 A 11/1999 Suzuki et al.
 5,991,690 A 11/1999 Murphy
 5,995,849 A 11/1999 Williams et al.
 6,002,363 A 12/1999 Krasner
 6,002,982 A 12/1999 Fry
 6,009,319 A 12/1999 Khullar et al.
 6,013,007 A 1/2000 Root et al.
 6,014,080 A 1/2000 Layson, Jr.
 6,014,090 A 1/2000 Rosen et al.
 6,018,704 A 1/2000 Kohli et al.
 6,023,241 A 2/2000 Clapper
 6,031,496 A 2/2000 Kuittinen et al.
 6,032,051 A 2/2000 Hall et al.
 6,034,622 A 3/2000 Levine
 6,054,928 A 4/2000 Lemelson et al.
 6,064,336 A 5/2000 Krasner
 6,067,018 A 5/2000 Skelton et al.
 6,067,044 A 5/2000 Whelan et al.
 6,072,396 A 6/2000 Gaukel
 6,078,290 A 6/2000 McBurney et al.
 6,083,248 A 7/2000 Thompson
 6,083,353 A 7/2000 Alexander, Jr.
 6,085,090 A 7/2000 Yee et al.
 6,094,168 A 7/2000 Duffett-Smith et al.
 6,100,806 A 8/2000 Gaukel
 6,101,710 A 8/2000 Selinger et al.
 6,104,334 A 8/2000 Allport
 6,111,540 A 8/2000 Krasner
 6,115,595 A 9/2000 Rodal et al.
 6,121,921 A 9/2000 Ishigaki
 6,125,325 A 9/2000 Kohli et al.
 6,131,067 A 10/2000 Girerd et al.
 6,140,863 A 10/2000 Fujisawa
 6,140,957 A 10/2000 Wilson et al.
 6,141,570 A 10/2000 O'Neill, Jr. et al.
 6,144,303 A 11/2000 Federman
 6,148,280 A 11/2000 Kramer
 6,154,422 A 11/2000 Shinkawa et al.
 6,163,696 A 12/2000 Bi et al.
 6,169,902 B1 1/2001 Kawamoto
 6,171,264 B1 1/2001 Bader
 6,172,640 B1 1/2001 Durst et al.
 6,175,616 B1 1/2001 Light et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,198,390 B1	3/2001	Schlager et al.	6,505,048 B1	1/2003	Moles et al.
6,198,431 B1	3/2001	Gibson	6,505,049 B1	1/2003	Dorenbosch
6,198,930 B1	3/2001	Schipper	6,512,456 B1	1/2003	Taylor, Jr.
6,199,045 B1	3/2001	Giniger et al.	6,513,532 B2	2/2003	Mault et al.
6,212,133 B1	4/2001	McCoy et al.	6,522,871 B1	2/2003	Patrick et al.
6,226,622 B1	5/2001	Dabbiere	6,522,889 B1	2/2003	Aarnio
6,231,519 B1	5/2001	Blants et al.	6,529,164 B1	3/2003	Carter
6,232,916 B1	5/2001	Grillo et al.	6,544,193 B2	4/2003	Abreu
6,236,358 B1	5/2001	Durst et al.	6,552,652 B2	4/2003	Beken
6,238,337 B1	5/2001	Kambhatla et al.	6,553,336 B1	4/2003	Johnson et al.
6,243,039 B1	6/2001	Elliot	6,559,620 B2	5/2003	Zhou et al.
6,243,660 B1	6/2001	Hsu et al.	6,560,463 B1	5/2003	Santhoff
6,246,376 B1	6/2001	Bork et al.	6,569,094 B2	5/2003	Suzuki et al.
6,252,543 B1	6/2001	Camp	6,571,193 B1	5/2003	Unuma et al.
6,252,544 B1	6/2001	Hoffberg	6,579,231 B1	6/2003	Phipps
6,259,944 B1	7/2001	Margulis et al.	6,579,844 B1	6/2003	Morrison et al.
6,263,280 B1	7/2001	Stingone, Jr.	6,611,688 B1	8/2003	Raith
6,266,612 B1	7/2001	Dussell et al.	6,625,437 B1	9/2003	Jampolsky et al.
6,272,457 B1	8/2001	Ford et al.	6,630,885 B2	10/2003	Hardman et al.
6,278,936 B1	8/2001	Jones	6,640,085 B1	10/2003	Chatzipetros et al.
6,281,797 B1	8/2001	Forster et al.	6,650,907 B1	11/2003	Kamperschroer et al.
6,282,362 B1	8/2001	Murphy et al.	6,661,372 B1	12/2003	Gierd et al.
6,282,495 B1	8/2001	Kirkhart et al.	6,679,071 B1	1/2004	Storey et al.
6,292,687 B1	9/2001	Lowell et al.	6,696,982 B2	2/2004	Yoshioka et al.
6,298,306 B1	10/2001	Suarez et al.	6,714,158 B1	3/2004	Underbrink et al.
6,300,875 B1	10/2001	Schafer	6,714,791 B2	3/2004	Friedman
6,302,844 B1	10/2001	Walker et al.	6,721,542 B1	4/2004	Anttila et al.
6,304,467 B1	10/2001	Nebrigic	6,741,927 B2	5/2004	Jones
6,314,308 B1	11/2001	Sheynblat et al.	6,747,675 B1	6/2004	Abbott et al.
6,317,049 B1	11/2001	Toubia et al.	6,748,318 B1	6/2004	Jones
6,323,807 B1	11/2001	Golding et al.	6,788,766 B2	9/2004	Logan
6,324,213 B1	11/2001	Harrison	6,801,853 B2	10/2004	Workman
6,327,533 B1	12/2001	Chou	6,804,606 B2	10/2004	Jones
6,330,149 B1	12/2001	Burrell	6,847,892 B2	1/2005	Zhou et al.
6,331,817 B1	12/2001	Goldberg	6,856,804 B1	2/2005	Ciotta
6,331,825 B1	12/2001	Ladner et al.	6,856,807 B1	2/2005	Raith
6,339,397 B1	1/2002	Baker	6,865,385 B1	3/2005	Kohda et al.
6,340,928 B1	1/2002	McCurdy	6,876,862 B1	4/2005	Tanaka
6,342,847 B1	1/2002	Archuleta et al.	6,888,879 B1	5/2005	Lennen
6,349,257 B1	2/2002	Liu et al.	6,937,900 B1	8/2005	Pianca et al.
6,353,390 B1	3/2002	Beri et al.	6,952,645 B1	10/2005	Jones
6,353,798 B1	3/2002	Green et al.	6,975,941 B1	12/2005	Lau et al.
6,356,836 B1	3/2002	Adolph	6,980,813 B2	12/2005	Mohi et al.
6,356,841 B1	3/2002	Hamrick et al.	6,980,826 B2	12/2005	Yamaguchi
6,362,778 B2	3/2002	Neher	6,997,882 B1	2/2006	Parker et al.
6,363,254 B1	3/2002	Jones et al.	7,010,144 B1	3/2006	Davis et al.
6,363,323 B1	3/2002	Jones	7,071,842 B1	7/2006	Brady, Jr.
6,366,871 B1	4/2002	Geva	7,085,253 B2	8/2006	Yang
6,373,430 B1	4/2002	Beason et al.	7,110,773 B1	9/2006	Wallace et al.
6,377,810 B1	4/2002	Geiger et al.	7,136,832 B2	11/2006	Li et al.
6,388,612 B1	5/2002	Neher	7,187,278 B2	3/2007	Biffar
6,393,346 B1	5/2002	Keith et al.	7,212,829 B1	5/2007	Lau et al.
6,404,352 B1	6/2002	Ichikawa et al.	7,218,938 B1	5/2007	Lau et al.
6,407,698 B1	6/2002	Ayed	7,253,731 B2	8/2007	Joao
6,411,892 B1	6/2002	Van Diggelen	7,308,272 B1	12/2007	Wortham
6,411,899 B2	6/2002	Dussell et al.	7,321,774 B1	1/2008	Lau et al.
6,421,538 B1	7/2002	Byrne	7,325,061 B2	1/2008	Haruki
6,426,719 B1	7/2002	Nagareda et al.	7,366,522 B2	4/2008	Thomas
6,427,120 B1	7/2002	Garin et al.	7,375,682 B1	5/2008	Tester et al.
6,430,602 B1	8/2002	Kay et al.	7,403,972 B1	7/2008	Lau et al.
6,433,732 B1	8/2002	Dutta et al.	7,482,920 B2	1/2009	Joao
6,434,396 B1	8/2002	Rune	7,539,557 B2	5/2009	Yamauchi
6,441,778 B1	8/2002	Durst et al.	7,809,377 B1	10/2010	Lau et al.
6,442,380 B1	8/2002	Mohindra	7,905,832 B1	3/2011	Lau et al.
6,442,391 B1	8/2002	Johansson et al.	7,953,809 B2	5/2011	Lau et al.
6,443,890 B1	9/2002	Schulze et al.	8,176,135 B2	5/2012	Lau et al.
6,445,937 B1	9/2002	daSilva	8,285,484 B1	10/2012	Lau et al.
6,453,237 B1	9/2002	Fuchs et al.	8,301,158 B1	10/2012	Thomas
6,463,272 B1	10/2002	Wallace et al.	8,447,822 B2	5/2013	Lau et al.
6,466,821 B1	10/2002	Pianca et al.	8,611,920 B2	12/2013	Lau et al.
6,469,639 B2	10/2002	Tanenhaus et al.	8,620,343 B1	12/2013	Lau et al.
6,471,087 B1	10/2002	Shusterman	8,700,050 B1	4/2014	Thomas
6,478,736 B1	11/2002	Mault	8,725,165 B2	5/2014	Lau et al.
6,484,034 B1	11/2002	Tsunehara et al.	8,753,273 B1	6/2014	Lau et al.
6,496,775 B2	12/2002	McDonald, Jr. et al.	8,868,103 B2	10/2014	Thomas
			8,886,220 B2	11/2014	Lau et al.
			8,975,941 B2	3/2015	Zierhofer
			9,049,571 B2*	6/2015	Lau H04W 4/12
			9,074,903 B1	7/2015	Lau et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,182,238 B2 11/2015 Lau et al.
 9,219,988 B2 12/2015 Lau et al.
 9,456,350 B2* 9/2016 Lau H04W 4/12
 2001/0006891 A1 7/2001 Cho
 2001/0020204 A1 9/2001 Runyon et al.
 2001/0027378 A1 10/2001 Tennison et al.
 2001/0027525 A1 10/2001 Gamlin
 2001/0028304 A1 10/2001 l'Anson et al.
 2001/0044299 A1 11/2001 Sandegren
 2001/0044332 A1 11/2001 Yamada et al.
 2001/0047125 A1 11/2001 Quy
 2001/0052849 A1 12/2001 Jones, Jr.
 2002/0000916 A1 1/2002 Richards
 2002/0000930 A1 1/2002 Crowson et al.
 2002/0008661 A1 1/2002 McCall et al.
 2002/0015439 A1 2/2002 Kohli et al.
 2002/0016173 A1 2/2002 Hunzinger
 2002/0027507 A1 3/2002 Yarin et al.
 2002/0028988 A1 3/2002 Suzuki et al.
 2002/0036593 A1 3/2002 Ying
 2002/0038182 A1 3/2002 Wong et al.
 2002/0049742 A1 4/2002 Chan et al.
 2002/0050945 A1 5/2002 Tsukishima et al.
 2002/0057192 A1 5/2002 Eagleson et al.
 2002/0063622 A1 5/2002 Armstrong et al.
 2002/0071677 A1 6/2002 Sumanaweera
 2002/0077080 A1 6/2002 Greene
 2002/0087260 A1 7/2002 Hancock et al.
 2002/0087619 A1 7/2002 Tripathi
 2002/0094067 A1 7/2002 August
 2002/0099567 A1 7/2002 Joao
 2002/0111171 A1 8/2002 Boesch et al.
 2002/0111819 A1 8/2002 Li et al.
 2002/0115453 A1 8/2002 Poulin et al.
 2002/0116080 A1 8/2002 Birnbach et al.
 2002/0119770 A1 8/2002 Twitchell, Jr.
 2002/0119789 A1 8/2002 Friedman
 2002/0120475 A1 8/2002 Morimoto
 2002/0120503 A1 8/2002 Iwayama et al.
 2002/0140081 A1 10/2002 Chou et al.
 2002/0173910 A1 11/2002 McCall et al.
 2002/0193121 A1 12/2002 Nowak et al.
 2002/0198003 A1 12/2002 Klapman
 2003/0003943 A1 1/2003 Bajikar
 2003/0009410 A1 1/2003 Ramankutty et al.
 2003/0013445 A1 1/2003 Fujiwara et al.
 2003/0018430 A1 1/2003 Ladetto et al.
 2003/0036389 A1 2/2003 Yen
 2003/0036683 A1 2/2003 Kehr et al.
 2003/0054827 A1 3/2003 Schmidl et al.
 2003/0068605 A1 4/2003 Kullok et al.
 2003/0069759 A1 4/2003 Smith
 2003/0083011 A1 5/2003 Haller et al.
 2003/0083046 A1 5/2003 Mathis
 2003/0083814 A1 5/2003 Gronemeyer
 2003/0095540 A1 5/2003 Mulligan et al.
 2003/0100326 A1 5/2003 Grube et al.
 2003/0107514 A1 6/2003 Syrjarinne et al.
 2003/0114206 A1 6/2003 Timothy et al.
 2003/0151507 A1 8/2003 Andre et al.
 2003/0163287 A1 8/2003 Vock et al.
 2003/0182052 A1 9/2003 DeLorme
 2003/0204132 A1 10/2003 Suzuki et al.
 2004/0034470 A1 2/2004 Workman
 2004/0046637 A1 3/2004 Wesby Van Swaay
 2004/0114731 A1 6/2004 Gillett et al.
 2004/0117108 A1 6/2004 Nemeth
 2004/0192352 A1 9/2004 Vallstrom et al.
 2004/0233065 A1 11/2004 Freeman
 2005/0250440 A1 11/2005 Zhou et al.
 2006/0173444 A1 8/2006 Choy et al.
 2007/0156286 A1 7/2007 Yamauchi
 2008/0021645 A1 1/2008 Lau et al.
 2008/0261636 A1 10/2008 Lau et al.
 2009/0042540 A1 2/2009 Bodnar et al.

2011/0022533 A1 1/2011 Lau et al.
 2011/0223884 A1 9/2011 Lau et al.
 2012/0220266 A1 8/2012 Lau et al.
 2013/0203388 A1 8/2013 Thomas et al.
 2013/0297524 A1 11/2013 Lau et al.
 2014/0011524 A1 1/2014 Lau et al.
 2014/0067708 A1 3/2014 Lau et al.
 2014/0273953 A1 9/2014 Lau et al.
 2014/0278084 A1 9/2014 Lau et al.
 2014/0296659 A1 10/2014 Lau et al.
 2015/0011243 A1 1/2015 Thomas et al.
 2015/0038168 A1 2/2015 Thomas et al.
 2015/0264576 A1 9/2015 Lau et al.
 2016/0025863 A1 1/2016 Lau et al.
 2016/0029175 A1 1/2016 Lau et al.
 2016/0050533 A1 2/2016 Lau et al.

FOREIGN PATENT DOCUMENTS

EP 1 037 477 A2 9/2000
 EP 1 037 477 A3 10/2001
 JP 09251069 A 9/1997
 JP 11-64482 3/1999
 JP 11-258325 9/1999
 JP 11-289574 10/1999
 JP 11-306491 11/1999
 JP 2001344678 A 12/2001
 WO WO 97/14054 4/1997
 WO WO 97/41654 A1 11/1997
 WO WO 98/01769 A1 1/1998
 WO WO 98/16045 A1 4/1998
 WO WO 98/40837 9/1998
 WO WO 00/51391 8/2000
 WO WO 01/50151 A1 7/2001
 WO WO 01/63318 A1 8/2001
 WO WO 01/75700 A2 10/2001
 WO WO 02/42979 A1 5/2002
 WO WO 02/084618 A1 10/2002
 WO WO 03/012720 A1 2/2003

OTHER PUBLICATIONS

Office Action for U.S. Appl. No. 10/397,474, dated Feb. 27, 2007.
 Office Action for U.S. Appl. No. 10/397,474, dated Sep. 6, 2007.
 Notice of Allowance for U.S. Appl. No. 10/397,474, dated Mar. 28, 2008.
 Restriction Requirement for U.S. Appl. No. 12/214,434, dated Nov. 16, 2010.
 Office Action for U.S. Appl. No. 12/214,434, dated Dec. 7, 2010.
 Notice of Allowance for U.S. Appl. No. 12/214,434, dated Feb. 9, 2011.
 Office Action for U.S. Appl. No. 13/113,972, dated Aug. 11, 2011.
 Notice of Allowance for U.S. Appl. No. 13/113,972, dated Nov. 28, 2011.
 Notice of Allowance for U.S. Appl. No. 13/113,972, dated Apr. 4, 2012.
 Office Action for U.S. Appl. No. 13/459,025, dated Sep. 13, 2012.
 Notice of Allowance for U.S. Appl. No. 13/459,025, dated Oct. 17, 2012.
 Notice of Allowance for U.S. Appl. No. 13/459,025, dated Apr. 8, 2013.
 U.S. Appl. No. 13/802,594, filed Mar. 13, 2013.
 Office Action for U.S. Appl. No. 13/802,594, dated May 8, 2014.
 Notice of Allowance for U.S. Appl. No. 13/802,594, dated Oct. 27, 2014.
 Notice of Allowance for U.S. Appl. No. 13/802,594, dated Feb. 2, 2015.
 Office Action for U.S. Appl. No. 14/727,798, dated Aug. 3, 2015.
 Notice of Allowance for U.S. Appl. No. 14/727,798, dated Jan. 5, 2016.
 Notice of Allowance for U.S. Appl. No. 14/727,798, dated Apr. 18, 2016.
 Notice of Allowance for U.S. Appl. No. 14/727,798, dated May 24, 2016.

(56)

References Cited

OTHER PUBLICATIONS

- “352C22 Miniature Low Profile ICP Accelerometer,” Precision Accelerometers, PCB Piezoelectronics Products—SVS Division, webpages, pp. 1-2 (downloaded Apr. 11, 2002: www.pcb.com/products/svs/svs352c22.html).
- “3G Mobile Internet Revolution, . . . only with Location Based Services!” pp. 1, (downloaded Aug. 10, 2002: <http://webhome.idirect.com/~dental/3glocator/home.htm>).
- “Airline Cargo Containers,” Case Study, RJI Incorporated, webpages, pp. 1-2 (downloaded Mar. 16, 2002: www.rji.cc/casestudies/airlinecargocounters.html).
- “Airline Food Carts,” Case Study, RJI Incorporated, webpages, pp. 1-2 (downloaded Mar. 16, 2002: www.rji.cc/casestudies/airlinefoodcarts.html).
- “An Introduction to SnapTrack Server-Aided GPS Technology,” SnapTrack Inc., Apr. 3, 2007. Archived page entitled “Money-Back Guarantee Policy” from fedex.com, archived by the Internet Archive on Aug. 17, 2000.
- “Audiovox Intros GPS, Bluetooth Phone,” INT Media Group, Inc. (allNetDevices), Apr. 5, 2002. (downloaded: www.allnetdevices.com/wireless/news/2001/1/15/audiovox_intros.html).
- “Carrier and end-user applications for wireless location systems,” TruePosition, Inc., http://www.trueposition.com/spie_app.htm, downloaded, Jul. 30, 2000, pp. 1-7.
- Capozza, P.T., et al. “A single-chip narrow-band frequency domain excisor for a Global Positioning System (GPS) receiver,” IEEE Journal of Solid-State Circuits, vol. 35, Issue 3, Mar. 2000, pp. 401-411.
- “Danger—Products” and “Hiptop Communicator Brochure,” Danger, Inc., downloaded Oct. 26, 2002: www.danger.com/products.php.
- “Developing a GPSs for the Global Supply Chain,” Aberdeen Group, Inc., Executive White Paper, Jun. 2002.
- “Devices for Text Messages in Deutsche Telekom’s fixed network have already found their way into many households,” Deutsche Telekom AG, Press Release, Mar. 13, 2002, pp. 1-2.
- “Digital/Analog Compass Sensors” and “1655 Digital Compass Sensor,” webpages, The Robson Company, Inc., pp. 1-2 (downloaded Apr. 11, 2002: www.dinsmoresensors.com/index.html).
- “EarthTrack™ Vehicle Tracking Systems,” Outfitter Satellite, Inc., 1998 (downloaded Jan. 22, 2000).
- “Enhanced Tracking,” United Parcel Service of America, Inc. (UPS), webpages, pp. 1-2 (downloaded Jun. 1, 2002: www.ups.com/myupsinfo/info/etrack?pnav=stdservice).
- “Fleet Management Systems—Asset Tracking Devices,” Axiom Navigation Inc., 2000-2001 (downloaded Oct. 19, 2002: www.axiomnav.com/Prod_Systems/prod_system.asp).
- “Frozen Food Warehouse,” Case Study, RJI Incorporated, webpages, pp. 1-3 (downloaded Mar. 16, 2002: www.rji.cc/casestudies/frozenfoodwarehouse.html).
- “FunMail Launches on the NTT DoCoMo i-mode network,” FunMail, Press Release, May 1, 2001, pp. 1-2.
- “Global Cell Phone Location,” Axiom Navigation Inc., 2000-2001 (downloaded Oct. 19, 2002: www.axiomnav.com/Prod_Global/prod_global.asp).
- “Global Locating Services,” SkyBitz, webpage, p. 1, (downloaded Nov. 15, 2002: www.skybitz.com/services/gls.html).
- “GLS Communicator,” SkyBitz, webpages, pp. 1-2, (downloaded Nov. 15, 2002: www.skybitz.com/gls/communicator.html).
- “Guide to Tracking Info.,” Nippon Express, website page, p. 1 (downloaded Jun. 9, 2002: www.nittsu.co.jp/edoc/howtoe.htm).
- “Introduction to SMS,” by C. Tull of Anywhere YouGo.com, pp. 1-4 (downloaded: www.devx.com/wireless/articles/SMS/SMSintro.asp), Aug. 10, 2002.
- “IO Data Develops GPS Adapter for I-Mode Mobile,” AsiaBizTech, Sep. 17, 2002, pp. 1-2.
- “Locate Networks: Our Service,” Locate Networks, webpages, pp. 1-7 (downloaded Sep. 26, 2002: www.locatenetworks.com/).
- “MMS phones: Don’t believe the hype,” CNN.com/SCI-TECH, Aug. 8, 2002, pp. 1-3.
- “Mobile Location Based Services: Cell Tracking Devices of People & Thongs . . .,” pp. 1-2, (downloaded Aug. 10, 2002: <http://3glocate.com>).
- “MoniTrack,” Case Study, RJI Incorporated, webpages, pp. 1-2 (downloaded Mar. 16, 2002: www.rji.cc/technology/telematic.html).
- “My ups.com Benefits,” United Parcel Service of America, Inc. (UPS), webpage, p. 1 (downloaded Apr. 13, 2002: www.ups.com/myupsinfo/info/benefits?pnav=stdservice).
- “NavMate® Navigation System,” Visteon Corporation, webpage, pp. 1-2 (downloaded Jun. 21, 2002: www.visteon.com/technology/automotive/navmate.html).
- “News,” SkyBitz, webpages, pp. 1-8, (downloaded Nov. 15, 2002: www.skybitz.com/about/news.html).
- “Pakhound: Your Watchdog in the Shipping Industry,” website pages, pp. 1-3 (downloaded Jun. 9, 2002: www.pakhound.com/fact.asp).
- “Parkwatch and Wherenet Unveil the First Amusement Visitor Locating system,” ParkWatch, Press Release, Jun. 27, 2000.
- “pulver.com’s Location Based Services Report,” pulver.com, Inc., Oct. 2001, pp. 1-17 (downloaded Jun. 4, 2002: www.pulver.com/lbsreport/lastbsreport.02/oct01.txt).
- “Radio Frequency Identification (RFID),” Case Study, RJI Incorporated, webpage, p. 1 (downloaded Mar. 16, 2002: www.rji.cc/technology/rfid.html).
- “Real Time Location System (RTLS),” Case Study, RJI Incorporated, webpage, p. 1 (downloaded Mar. 16, 2002: www.rji.cc/technology/rtls.html).
- “Real-Time Warehouse Tracking,” Case Study, RJI Incorporated, webpages, pp. 1-2 (downloaded Mar. 16, 2002: www.rji.cc/casestudies/rtwarehousetracking.html).
- “Savi Reusable Transport Container,” Savi Technology, Inc., Apr. 30, 2002, pp. 1-2.
- “Send images to i-mode phones,” Mobile Media Japan, 2001, pp. 1-3.
- “Ski Rental with Auto ID and Tracking,” Case Study, RJI Incorporated, webpages, pp. 1-2 (downloaded Mar. 16, 2002: www.rji.cc/casestudies/skirentalcompany.html).
- “SnapTrack and SignalSoft Corp. Team Up to Trial Location-based Information Service for GSM Test Group,” Press Release, SnapTrack Inc., Dec. 6, 1999.
- “SnapTrack Awarded Additional Key Patents for Enhanced GPS System,” Press Release, SnapTrack Inc., Jan. 4, 2000.
- “Start-up crams single chip with phone, GPS and Bluetooth,” CNET Network, Inc. (ZDNET), Mar. 22, 2002 (downloaded: <http://news.zdnet.co.uk/story/0,t284-x2107163,00.html>).
- “Status Icons/Messages,” Yahoo! Messenger Help, Yahoo! Inc., 2002, pp. 1-2.
- “Technical Applications of Our Current Technology,” Aetherwire, webpages, pp. 1-4 (downloaded Mar. 16, 2002: www.aetherwire.com/CDROM/General/appl1.html).
- “The Always on Network,” Position Paper, Nortel Networks, 2002.
- “Theme Park Visitors & Cashless Purchasing,” Case Study, RJI Incorporated, webpages, pp. 1-2 (downloaded Mar. 16, 2002: www.rji.cc/casestudies/themepark.html).
- “Track Shipments—Detailed Results,” FedEx, webpages, pp. 1-2 (downloaded Oct. 29, 2002: www.fedex.com).
- “Track Your FedEx Shipments via Email,” FedEx, webpages, pp. 1-2 (downloaded Oct. 29, 2002: www.fedex.com).
- “Tracking Helpful Tips,” United Parcel Service of America, Inc. (UPS), webpages, pp. 1-2 (downloaded Jun. 1, 2002: www.ups.com/tracking/nm_help.html).
- “Trimble and Rosum Team to Develop Universal Positioning Technology,” Trimble Navigation, Inc., News Release, Feb. 27, 2003.
- “Turning Position Into Knowledge,” SkyBitz, webpage, p. 1, (downloaded Nov. 15, 2002: www.skybitz.com).
- “UPS Package Tracking,” United Parcel Service of America, Inc. (UPS), webpages, pp. 1-2 (downloaded Apr. 13, 2002: www.ups.com/tracking/tracking.html).
- “UPS Wireless Solutions,” United Parcel Service of America, Inc. (UPS), webpage, p. 1 (downloaded Apr. 13, 2002: www.ups.com/myupsinfo/info/wireless?pnav=stdservice).

(56)

References Cited

OTHER PUBLICATIONS

- "Welcome to Iship, Inc.," iShip, Inc., webpages, pp. 1-2, (downloaded Jun. 9, 2002: www.iship.com/).
- "Welcome to Traker Systems," Tracker Systems, webpages, pp. 1-2 (downloaded Jun. 9, 2002: www.trakersystems.com/).
- "What are Instant Messages?" Yahoo! Messenger Help, Yahoo! Inc., 2002, pp. 1.
- "What is '3G' technology?" CNN.com/SCI-TECH, Oct. 22, 2001, pp. 1-3.
- "What is a Friend List?" Yahoo! Messenger Help, Yahoo! Inc., 2002, pp. 1.
- "Wherify Wireless and SiRF Team to Deliver Child Locator System," Wherify Wireless, Inc., Press Release, Mar. 19, 2001, pp. 1-2.
- "Wherify Wireless Breakthrough in Location-Based Services," Mobilemag.com, Feb. 28, 2001, p. 1.
- "Wherify Wireless GPS Locator for Kids User Guide," Wherify Wireless, Inc., 2003, pp. 1-106.
- "Wherify Wireless Location Services," Wherify Wireless, Inc., webpages, pp. 1-5 (downloaded: Mar. 25, 2003: www.wherifywireless.com/prod_watches.htm).
- "X-GPS™—Hybrid GPS Location Server Solution," Axiom Navigation Inc., 2000-2001 (downloaded Oct. 19, 2002: www.axiomnav.com/Prod_Global/x-gps.asp).
- "Yahoo! Messenger—Sending Messages to a Mobile Phone," Yahoo! Messenger, Yahoo! Inc., 2002, pp. 1-7 (downloaded Oct. 27, 2002: [http://messenger.yahoo.com/messenger/wireless/pc2sms/tour1.html\(through_tour7.html\)](http://messenger.yahoo.com/messenger/wireless/pc2sms/tour1.html(through_tour7.html))).
- "Yahoo! Messenger for Text Messaging," Yahoo! Messenger, Yahoo! Inc., 2002, pp. 1-10 (downloaded Oct. 27, 2002: [http://messenger.yahoo.com/messenger/wireless/smsmsg/tour1.html\(through_tour7.html\)](http://messenger.yahoo.com/messenger/wireless/smsmsg/tour1.html(through_tour7.html))).
- "Yahoo! Messenger for WAP," Yahoo Messenger, Yahoo! Inc., 2002 (tours 1-9), pp. 1-17 (downloaded Oct. 27, 2002: [www.messenger.yahoo.com/messenger/wireless/wap/tour1.html\(through_tour9.html\)](http://www.messenger.yahoo.com/messenger/wireless/wap/tour1.html(through_tour9.html))).
- Accelerometers—General Purpose, LP Series, Crossbow Technology, Inc., data sheet, pp. 1-3 (downloaded Apr. 11, 2002: www.xbow.com/Products/Accelerometers.htm).
- Bickers, "Eyes in the sky," SafeTzone Technology Corporation, webpages, 2001, pp. 1-3 (downloaded: www.safetzone.com/newsKiosk.asp).
- Chertkoff, Rachel, "Vehicle Locator Systems," Pager Technology, pp. 1-2, 1998.
- Commercial Uses for LoJack (webpage), LoJack Corporation, downloaded Jan. 22, 2000.
- Crossbow Product Guide—Accelerometers, Crossbow Technology, Inc., webpages, pp. 1-3 (downloaded Apr. 11, 2002: www.xbow.com/Products/Accelerometers.htm).
- Culler, D. et al., "MICA: The Commercialization of Microsensor Nodes," *Sensors* (Apr. 1, 2002), pp. 1-5.
- Darabi et al. "A 2.4-GHz CMOS Transceiver for Bluetooth," *IEEE Journal of Solid-State Circuits*, vol. 36, No. 12 (Dec. 2001), pp. 2016-2024.
- Delphi and MobileAria Demonstrate True Hands Free In-Vehicle Mobile Productivity Services at CES, Press Release, Delphi Automotive Systems, Jan. 8, 2002 (downloaded Apr. 5, 2002: www.delphiauto.com/news/pressRelease/pr6828-01082002).
- F. Rivera, "Special Report: Keeping Tabs on Your Teen," *7 News*, Boston, Apr. 30, 2002, pp. 1-3.
- FedEx Insight, FedEx, webpages, pp. 1-11 (downloaded Oct. 29, 2002: www.fedex.com).
- Fraden, J., *Handbook of Modern Sensors: Physics, Designs and Applications*, Second Edition, Springer-Verlag (1996), cover, pp. 310-354, 384-431, 458-493, and 513-528.
- GPS2000, Omega Research and Development, Inc., webpages, pp. 1-9 (pp. 7-9 pertain to an online tour) (downloaded Jul. 14, 2003: www.gps2000online.com/).
- Grimes, et al. "Wireless Magnetoelastic Resonance Sensors: A Critical Review," *Sensors*, vol. 2 (Jul. 23, 2002), pp. 294-313.
- Helfenstein et al. *Circuits and Systems for Wireless Communications*, Kluwer Academic Publishers (2000), cover pages, pp. 3-7, 9-34, and 37-47.
- Hill et al. "System Architecture Directions for Networked Sensors," *ACM/ASPLOS-IX* (Nov. 2000), 12 pages.
- IMVironment, Yahoo! Messenger Yahoo! Inc., 2002, pp. 1-12 (downloaded (including) Oct. 27, 2002: [http://help.yahoo.com/help/us/mesg/imv/imv-01.html\(through_index5.html\)](http://help.yahoo.com/help/us/mesg/imv/imv-01.html(through_index5.html))).
- J.Wrolstad, "Chrysler Claims First With Bluetooth Mobile Phone System," *Wireless Newsfactor*, Oct. 26, 2001.
- K. Hill, "Prada Uses Smart Tags to Personalize Shopping," *CRMDaily.com*, Apr. 24, 2002., pp. 1-4.
- Madou, Marc J., *Fundamentals of Microfabrication: The Science of Miniaturization*, Second Edition, CRC Press (2002) 139 pages.
- K. Miyake, "Sharp to unveil 3G PDA-type cell phone," *ITworld.com, Inc.*, Jan. 11, 2002.
- Kleinknecht, William, "Juvenile authorities want satellite tracking for felons," *The Star-Ledger of New Jersey*, Nov. 18, 1997.
- LoadTrak, pp. 1-2 (downloaded Jun. 4, 2002: www.load-trak.com).
- Mainwaring et al., "Wireless Sensor Networks for Habitat Monitoring," *ACM* (Sep. 28, 2002) pp. 88-97.
- Marek, "The Unstoppable SnapTrack," *Wireless Week*, Dec. 18, 2000.
- Motorola Consumer Catalog: Pagers (webpage), Motorola, Inc., downloaded Jan. 19, 2000.
- My.Roadway! Roadway Express, Inc., webpages, pp. 1-2, (downloaded Jun. 9, 2002: www.quiktrak.roadway.com/cgi-bin/quiktrak).
- Package, Dictionary.com, <http://dictionary.reference.com/browse/package> (last accessed Nov. 6, 2013), 3 pgs.
- "Package" definition, *Oxford English Dictionary (OED) Online*, Oxford University Press, Jun. 2014 (printed Aug. 1, 2014).
- "Portable" definition, *Oxford English Dictionary (OED) Online*, Oxford University Press, Jun. 2014 (printed Aug. 1, 2014).
- Packtrack™, PackTrack.com, webpages, pp. 1-2 (downloaded Jun. 9, 2002: www.packtrack.com).
- Precision Accelerometers, PCB Piezoelectronics Products—SVS Division, webpages, pp. 1-2 (downloaded Apr. 11, 2002: www.pcb.com/products/sys/index.html).
- Rabinowitz and Spilker, Jr., "A New Positioning System Using Television Synchronization Signals," Rosum Corporation, pp. 1-11 (downloaded May 21, 2003).
- Rabinowitz and Spilker, Jr., "Positioning Using the ATSC Digital Television Signal," Rosum Corporation Whitepaper, Rosum Corporation (downloaded May 21, 2003).
- Razavi, Behzad, *RF Microelectronics*, Prentice Hall (1998), cover pages, pp. 1-10, and 118-297.
- Real Time Locating System, Executive Summary, Technology Systems International, Inc., 2007.
- Rofougaran et al. "A Single-Chip 900-MHz Spread-Spectrum Wireless Transceiver in 1- μ m CMOS—Part II: Receiver Design," *IEEE Journal of Solid-State Circuits*, vol. 33, No. 4 (Apr. 1998), pp. 535-547.
- Ryan, "Catching up with Dick Tracy," *San Francisco Chronicle*, news article, Mar. 18, 2002.
- SandPiper GPS Receiver, Specification sheet by Axiom Navigation Inc. (www.axiomnav.com) 2006.
- Senturia, Stephen D., *Microsystem Design*, Kluwer Academic Publishers (2001), cover pages, and pp. 3-14.
- SiRF Debuts Revolutionary Architecture and Technologies to Further Drive GPS into the Mainstream, SiRF.com, Aug. 16, 1999 (archived Dec. 22, 1999), http://web.archive.org/web/19991222194810/http://www.sirf.com/as_prss2_3.htm, 4 pgs.
- Smart Antenna, Specification sheet by Axiom Navigation Inc. (www.axiomnav.com) 2008.
- SnapTrack—Privacy Protection (webpage), SnapTrack Inc., downloaded Jan. 19, 2000.
- SnapTrack—Technology At Work (webpage), SnapTrack Inc., downloaded Jan. 19, 2000.
- SnapTrack in Action (webpage), SnapTrack Inc., downloaded Jan. 19, 2000.
- Steyaert et al., "A 2-V CMOS Cellular Transceiver Front-End," *IEEE Journal of Solid-State Circuits*, vol. 35, No. 12, Dec. 2000, pp. 1895-1907.

(56)

References Cited

OTHER PUBLICATIONS

- Stilp, Louis A., "Examining the Coming Revolution in Location Services," pp. 1-11.
- Strom, Stephanie. "A Wild Sleigh Ride at Federal Express," *The New York Times*, Dec. 20, 1994.
- Swift A2 GPS Receiver, Specification sheet by Axiom Navigation Inc. (www.axiomnav.com) 2010.
- Swift B2 GPS Receiver, Specification sheet by Axiom Navigation Inc. (www.axiomnav.com) 2010.
- TruePosition Virtual Brochure (webpage), TruePosition, Inc.
- Wong, "Fishers, golfers join the rush to GPS," *San Jose Mercury News*, news article, Mar. 25, 2002.
- Danger Product Overview, Danger, Inc., date unknown, 5 pgs.
- PCVtrak™ Installation and Operator's Manual, Trimble Navigation, 24623-00 Rev. A, May 1994, pp. 1-259.
- "Advanced Traveler Aid Systems for Public Transportation," Final Report, Federal Transit Administration, Sep. 1994, pp. 1-131.
- Campbell, Laurel, "SECURITY—Military satellite enlisted to thwart car crime," *The Commercial Appeal*, Sep. 26, 1996, pp. 5B.
- Law, Alex, "Week in Wheels/ . . . From a Driver's Notebook," *Newsday, Inc.*, Sep. 20, 1996, pp. C03.
- Cortez, Angela, "Springs police can track thief, vehicles," *The Denver Post*, Sep. 10, 1996, pp. B-01.
- "OnGuard Tracker Nabs Auto Burglar," *Global Positioning & Navigation News*, vol. 6, No. 16, Aug. 8, 1996.
- "OnGuard Tracker Nabs Auto Burglar," Section: Financial News, *PR Newswire*, Jul. 29, 1996.
- Nauman, Matt, "Pressing the Panic Button: Car Security Enters a New Age with Cellular Phones and Satellites that Watch Over You," *San Jose Mercury News*, Jun. 21, 1996, pp. 1G.
- "Monday Briefing" *San Antonio Express-News*, p. 1, Part B, Jun. 10, 1996.
- "OnGuard Tracker Makes Debut on 'One Lap of America'," *PR Newswire*, Jun. 7, 1996.
- "OnGuard Tracker Makes Debut on 'One Lap of America'," *Southwest Newswire*, Jun. 7, 1996.
- Dominguez, Raul, "Women get their day in sun—American Golf planning events nationwide May 18," *San Antonio Express-News*, Apr. 18, 1996, pp. 2, part B.
- "Vehicle Navigation Units Being Measured in Luxury Autos," *Global Positioning & Navigation News*, vol. 6, No. 7, Apr. 4, 1996.
- "Advanced Business Sciences, Inc. Announces Completion of Acquisition of Comguard of Illinois," *Business Wire*, Aug. 26, 1998.
- "Advanced Business Sciences, Inc. Announces Filing With Securities and Exchange Commission," *Business Wire*, Jun. 25, 1999.
- "Advanced Business Sciences, Inc. Announces Preliminary Fourth Quarter 1998 Revenue Results," *Business Wire*, Feb. 4, 1999.
- "Business People Burnsy's Grill Names Two," *Omaha World-Herald*, Section Business, p. 4M, Oct. 20, 1996.
- "Company Sees Prisoner Tracking and Monitoring Market Niche," *Global Positioning & Navigation News*, vol. 6, No. 10, May 16, 1996.
- GPS-Based Personal Monitoring Systems Offered to Corrections, Private Market, *Global Positioning & Navigation News*, vol. 8, No. 11, Jun. 3, 1998.
- GPS tracks parolees, probationers, *Corrections Professional*, vol. 5, No. 6, Nov. 19, 1999.
- High-Tech System Tracks Offenders—Satellites Watching Criminals, *Business Wire*, Nov. 14, 1997.
- Briefs, *Global Positioning & Navigation News*, vol. 9, No. 4, Feb. 24, 1999.
- Dunkelberger, Lloyd, "Lawmakers question criminal-tracking system," *Sarasota Herald-Tribune (Florida)*, pp. 16A, Nov. 28, 1999.
- Powell, Barbara. "New gadgets help drivers find their way," *Fort Worth Star-Telegram (Texas)*, p. 1, Jan. 20, 1997.
- "New Service Lets Corrections Agencies Track Offenders by Satellite," *PR Newswire*, Jan. 11, 1999.
- "New Service Lets Corrections Agencies Track Offenders by Satellite; SecurityLink Offers 'GPS' Tracking for Offenders on Electronic Monitoring—Sandusky Municipal Court Adopts Technology for Local Offenders," *PR Newswire*, Jan. 12, 1999.
- "New Service Lets Corrections Agencies Track Offenders by Satellite; SecurityLink Offers 'GPS' Tracking for Offenders on Electronic Monitoring," *PR Newswire*, Section: Financial News, Jan. 11, 1999.
- "New Service Lets Corrections Agencies Track Offenders by Satellite," *Satellite Today*, vol. 2, No. 8, Jan. 13, 1999.
- "Prisoner Security Monitoring Company Grabs Contracts for GPS-Based System," *Global Positioning & Navigation News*, vol. 7, No. 1, Jan. 15, 1997.
- Atwater, Andi, "Proposal seeking 24-hour tracking of all sex offenders," *The News-Press (Fort Meyers, FL)*, pp. 1A, Feb. 20, 2000.
- Briefs, *Global Positioning & Navigation News*, vol. 9, No. 3, Feb. 10, 1999.
- Brauer, David, "Satellite 'Big Brother' Tracks Ex-Inmates; Agencies Experiment with GPS to Monitor Parolee Whereabouts," *Chicago Tribune*, Section: News, p. 31, Dec. 18, 1998.
- "Satellite Spotlight; Eye in the Sky to Monitor Parolees," *Satellite News*, vol. 21, No. 15, Apr. 13, 1998.
- "Satellite Spotlight: Fighting Crime From Space," *Satellite News*, vol. 19, No. 20, May 13, 1996.
- Prohaska, Thomas J, "Satellite Will Keep Tabs on Convicts," *Buffalo News (New York)*, Section: Local, p. 5B, Sep. 20, 1999.
- "Sierra Wireless and Pro Tech Team Up on Monitoring Product," *Global Positioning & Navigation News*, vol. 8, No. 8, Apr. 22, 1998.
- Anderson, Larry, "Technology rules at Securing New Ground," *Access Control & Security Systems Integration*, Section: Industry Outlook; ISSN 1084-6425, Dec. 1999.
- Trimble Navigation Warns 2nd-Quarter Earnings to Miss Target, *Dow Jones Business News*, Jul. 10, 1998.
- "Trimble Navigation's Net Income Skidded 93% Amid Order Delays," *Dow Jones Business News*, Jul. 23, 1998.
- Briefs, *Global Positioning & Navigation News*, vol. 9, No. 2, Jan. 27, 1999.
- Briefs, *Global Positioning & Navigation News*, vol. 9, No. 14, Jul. 14, 1999.
- Dailey et al. "Automatic Transit Location System," Final Research Report, 55 pgs., Feb. 1996.
- Maguire, Jr. et al. "SmartBadges: a wearable computer and communication system," codes/CASHE '98, 47 pgs., 1998.
- Koshima et al. "Personal locator services emerge," *IEEE Spectrum*, Feb. 2000, pp. 41-48.
- Zygowicz et al. "State of the Art in Automatic Vehicle Location Systems," Center for Urban Transportation Studies, University of Wisconsin, Milwaukee, Feb. 1998.
- Ashworth, Jon. "Big brother is watching you," *The Times (London)*, Section: Features, May 7, 1999.
- "Car Thieves Take the 'Bait' in Michigan; Two Suspects Reeled in With OnGuard," *Business Wire*, Sep. 11, 1997.
- Sauer, Matthew, "Company Finds Niche by Giving Directions . . ." *Sarasota Herald-Tribune (Florida)*, Section: Business Weekly, p. 1, Jul. 7, 1997.
- "ATX Technologies Signs Nationwide Service Deal with AT&T," *Global Positioning & Navigation News*, vol. 7, No. 9, May 7, 1997.
- "Car Thieves Take the 'Bait' in Tulsa; Two Suspects Caught Off Guard with OnGuard Once Again," *PR Newswire*, Section: Financial News, Jan. 8, 1997.
- "Car Thieves Take the 'Bait' in Tulsa; Two Suspects Caught Off Guard with on Guard," *PR Newswire*, Section: Financial News, Dec. 9, 1996.
- Jackson, Terry, "Smart Cars Whether by Satellite or the Internet, High-Tech Devices and Services May Make Crumpled Road Maps a Thing of the Past," *The Miami Herald*, Section: Travel, p. 1J, Oct. 6, 1996.
- "San Antonio Personal Security Company Links Up with Senior PGA Golfer," *PR Newswire*, Section: Financial News, Apr. 1, 1996.
- "San Antonio Personal Security Company Links Up with Senior PGA Golfer," *Southwest Newswire*, Apr. 1, 1996.
- Business Briefs, *San Antonio Express-News*, Mar. 25, 1996.
- "ATX Research Signs Exclusive Sales Agreement with Arizona Company," *PR Newswire*, Mar. 21, 1996.

(56)

References Cited

OTHER PUBLICATIONS

"ATX Research Signs Exclusive Sales Agreement with Arizona Company," Southwest Newswire, Mar. 21, 1996.

"Automotive GPS Satellite/Safety System Race Is On," Southwest Newswire, Feb. 20, 1996.

"Dealerships Can Track Down New Aftermarket Revenues," PR Newswire, Feb. 9, 1996.

"ATX Research Unveils New Stealthtrac Capability," PR Newswire, Feb. 9, 1996.

"Dealerships Can Track Down New Aftermarket Revenues," Southwest Newswire, Feb. 9, 1996.

Briefs, Global Positioning & Navigation News Wire, vol. 6, No. 2, Jan. 24, 1996.

"ATX Research Provides Police Departments With Onguard Personal Security and Vehicle Tracking System," PR Newswire, Jan. 15, 1996.

"ATX Research Provides Police Departments With Onguard Personal Security and Vehicle Tracking System," Southwest Newswire, Jan. 15, 1996.

"ATX Research Relocates to New Corporate Headquarters," PR Newswire, Dec. 12, 1995.

"ATX Research Relocates to New Corporate Headquarters," Southwest Newswire, Dec. 12, 1995.

"Texas invention tracks stolen cars, lets driver call for help," The Vancouver Sun, Oct. 20, 1995.

"San Antonio Company Unveils Satellite/Cellular Personal Security System," PR Newswire, Oct. 3, 1995.

"San Antonio Company Unveils Satellite/Cellular Personal Security System," Southwest Newswire, Oct. 3, 1995.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

**METHOD AND SYSTEM FOR ENHANCED
MESSAGING****CROSS REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 14/727,798, filed Jun. 1, 2015, and entitled "METHOD AND SYSTEM FOR ENHANCED MESSAGING," (now U.S. Pat. No. 9,456,350), which is hereby incorporated by reference, which in turn is a continuation of U.S. patent application Ser. No. 13/802,594, filed Mar. 13, 2013, and entitled "METHOD AND SYSTEM FOR ENHANCED MESSAGING," (now U.S. Pat. No. 9,049,571), which is hereby incorporated by reference, which in turn is a continuation of U.S. patent application Ser. No. 13/459,025, filed Apr. 27, 2012, and entitled "METHOD AND SYSTEM FOR ENHANCED MESSAGING," (now U.S. Pat. No. 8,447,822), which is hereby incorporated by reference, which in turn is a continuation of U.S. patent application Ser. No. 13/113,972, filed May 23, 2011, and entitled "METHOD AND SYSTEM FOR ENHANCED MESSAGING," (now U.S. Pat. No. 8,176,135), which is hereby incorporated by reference, which in turn is a continuation of U.S. patent application Ser. No. 12/214,434, filed Jun. 19, 2008, and entitled "METHOD AND SYSTEM FOR ENHANCED MESSAGING," (now U.S. Pat. No. 7,953,809), which is hereby incorporated herein by reference, which in turn is a continuation of U.S. patent application Ser. No. 10/397,474, filed Mar. 26, 2003, and entitled "METHOD AND SYSTEM FOR ENHANCED MESSAGING," (now U.S. Pat. No. 7,403,972), which is hereby incorporated herein by reference, and which in turn claims benefit of: (i) U.S. Provisional Patent Application No. 60/444,198, filed Jan. 30, 2003, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MONITORING, DELIVERING, MANAGING AND USING STATUS INFORMATION," which is hereby incorporated herein by reference; (ii) U.S. Provisional Patent Application No. 60/418,491, filed Oct. 15, 2002, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MONITORING, DELIVERING, MANAGING AND USING STATUS INFORMATION," which is hereby incorporated herein by reference; (iii) U.S. Provisional Patent Application No. 60/404,645, filed Aug. 19, 2002, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MONITORING, DELIVERING, MANAGING AND USING POSITION AND OTHER INFORMATION," which is hereby incorporated herein by reference; and (iv) U.S. Provisional Patent Application No. 60/375,998, filed Apr. 24, 2002, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MANAGING AND USING POSITION INFORMATION," which is hereby incorporated herein by reference.

This application is also related to: (i) U.S. patent application Ser. No. 10/397,473, filed Mar. 26, 2003, and entitled "METHOD AND APPARATUS FOR INTELLIGENT ACQUISITION OF POSITION INFORMATION," (now U.S. Pat. No. 6,975,941); (ii) U.S. patent application Ser. No. 10/397,472, filed Mar. 26, 2003, and entitled "METHODS AND APPARATUS TO ANALYZE AND PRESENT LOCATION INFORMATION," (now U.S. Pat. No. 7,218,938); (iii) U.S. patent application Ser. No. 10/397,637, filed Mar. 26, 2003, and entitled "METHOD AND SYSTEM FOR PROVIDING SHIPMENT TRACKING AND NOTIFICATIONS," (now U.S. Pat. No. 7,212,829); (iv) U.S.

2

patent application Ser. No. 10/397,641, filed Mar. 26, 2003, and entitled "METHOD AND SYSTEM FOR PERSONALIZED MEDICAL MONITORING AND NOTIFICATIONS THEREFOR," (now U.S. Pat. No. 7,905,832); (v) U.S. patent application Ser. No. 10/397,640, filed Mar. 26, 2003, and entitled "INEXPENSIVE POSITION SENSING DEVICE," (now U.S. Pat. No. 7,321,774); (vi) U.S. patent application Ser. No. 10/397,512, filed Mar. 26, 2003, and entitled "APPLICATIONS OF STATUS INFORMATION FOR INVENTORY MANAGEMENT."

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to communication devices and, more particularly, to enhanced messaging for communication devices.

2. Description of the Related Art

Today, electronic mail (email) is a common mode of communication. One person, acting as a sender, composes an email message and then sends the email message to another person designated as a recipient. The sender composes the email message by interacting with a communication device. The recipient is able to read the email message by interacting with another communication device. Communication devices are often personal computers or mobile telephones. These communication devices can receive and transmit electronic mail messages over a network. The network can be public or private as well as wired or wireless.

Although email is an effective means of communication, when a sender is using a mobile telephone, composing an email message can be tedious and difficult. User interfaces can provide limited assistance to users such as by creating email messages through word prediction, predetermined responses, etc. Nevertheless, given the difficulties with composing messages, email messages from mobile telephones in most cases are relatively short. Recently, communication devices, including mobile telephones, have been able to send and receive instant messages, which are short text messages sent and received in near real time between communication device.

Apart from sending and receiving email messages, mobile telephones can also display the location or availability (i.e., online or offline) of other users via their mobile telephones. This information is provided by a wireless service provider that monitors location or availability of users via their mobile phones. Unfortunately, such information needs the assistance of wireless service providers and tends not to be widely available. Moreover, if such information is available, the information would very likely not be current and thus the usefulness of the information would be limited.

Thus, there is a need for improved approaches to enhance the capabilities of messaging.

SUMMARY

Broadly speaking, the invention relates to techniques for acquiring, sending, receiving or using status information from a remote location over a network. The status information is transmitted by electronic devices over the network. The status information can be provided by one or more sensors associated with the electronic device that is transmitting the status information. The status information can be transmitted with messages so as to enhance the messages.

According to one aspect of the invention, base messages are entered by a user or automatically produced. The base messages can be text messages (including instant messages),

voice messages, video messages or other types of messages. The base messages are augmented to additionally include status information, such as position and/or other conditions information. The status information is normally provided by one or more sensors. In one implementation, base messages can be combined with status information, whereby the resulting messages are referred to as enhanced messages. These enhanced messages are electronically sent from and received at electronic devices, such as personal computers and mobile communication devices.

The invention can be implemented in numerous ways including, a method, system, device, graphical user interface, and a computer readable medium. Several embodiments of the invention are discussed below.

As a method to facilitate communication among users of mobile electronic devices user communication system for communicating between users of mobile communication devices, one embodiment of the invention can, for example, include at least the acts of: receiving message content for a text message via the first mobile electronic device; acquiring status information of the first mobile electronic device, the status information including at least position information associated with the first mobile electronic device; determining a plurality of other mobile electronic devices or users thereof that are authorized to receive the message content and the status information; determining whether at least one user selection has been provided via the first mobile communication device to indicate whether the status information is to be provided with the text message, and initiating sending of the text message including the message content along with the status information to each of the plurality of other mobile electronic devices via a wireless network, provided that it is determined that the status information is to be provided with the text message and provided that the plurality of other mobile electronic devices or users thereof are authorized to receive the text message.

As a computer readable medium including at least computer program code tangible stored thereon for facilitating communication among users of mobile electronic devices, one embodiment of the invention can, for example, include at least: computer program code for receiving message content for a text message via the first mobile electronic device; computer program code for acquiring status information of the first mobile electronic device, the status information including at least position information regarding position of the first mobile electronic device; computer program code for determining a plurality of other mobile electronic devices or users thereof that are authorized to receive the status information; computer program code for determining whether at least one indication has been received from the first mobile communication device to influence whether the status information is to be provided with the text message; computer program code for determining based at least in part on the at least one indication whether the status information is to be provided with the text message, and computer program code for initiating sending of the text message along with the status information to each of the plurality of other mobile electronic devices via at least one wireless network, provided that it is determined that the status information is to be provided with the text message and provided that the plurality of other mobile electronic devices or users thereof are authorized to receive the status information.

As a method for providing communications between computing devices, another embodiment of the invention includes at least the acts of: obtaining a message at a first mobile communication device to be delivered to a second

mobile communication device; determining whether status information is to accompany the message; sending the message without any status information when it is determined that status information is not to accompany the message; and acquiring status information at the first mobile communication device and then sending the message and the status information to the second mobile communication device when it is determined that status information is not to accompany the message.

As a method for displaying a message on a display device of a computing device, one embodiment of the invention includes at least the acts of: receiving a message from another computing device over a network; determining whether the message includes at least status information; extracting the status information from the message when it is determined that the message includes at least the status information; and displaying the message and at least one representation of the status information on the display device following the extracting when it is determined that the message includes at least the status information.

As a method for displaying a message on a display device of a computing device, another embodiment of the invention includes at least the acts of: receiving a message from another computing device over a network; determining whether the message includes at least status information; extracting the status information from the message when it is determined that the message includes at least the status information; and displaying the message and at least one representation of the status information on the display device following the extracting when it is determined that the message includes at least the status information.

Other aspects and advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements, and in which:

FIG. 1 is a block diagram of an enhanced messaging system according to one embodiment of the invention.

FIG. 2 is a block diagram of an enhanced messaging system according to another embodiment of the invention.

FIG. 3 is a flow diagram of status message processing according to one embodiment of the invention.

FIG. 4 is a flow diagram of send processing according to one embodiment of the invention.

FIG. 5 is a flow diagram of display processing according to one embodiment of the invention.

FIG. 6 is a flow diagram of status retrieval processing according to one embodiment of the invention.

FIG. 7 is a flow diagram of status request processing according to one embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

The invention relates to techniques for acquiring, sending, receiving or using status information from a remote location over a network. The status information is transmitted over the network between or among electronic devices. The status information can be provided by one or more sensors associated with the electronic device that is transmitting the status information. The status information can be transmit-

ted with messages so as to enhance the messages. The electronic devices include at least computing devices, such as personal computers, personal digital assistants, pagers, and mobile telephones.

According to one aspect of the invention, messages are enhanced through use of status information. Base messages are entered by a user or automatically produced. The base messages can be text messages (including instant messages), voice messages, video messages or other types of messages. The base messages are augmented to additionally include status information, such as position and/or other conditions information. The status information is normally provided by one or more status sensors. In one implementation, base messages can be combined with status information, whereby the resulting messages are referred to as enhanced messages. These enhanced messages are electronically sent from and received at communication devices, such as personal computers and mobile communication devices.

Different embodiments of the invention are discussed below with reference to FIGS. 1-7. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these figures is for explanatory purposes as the invention extends beyond these limited embodiments.

According to one aspect of the invention, traditional messages transmitted between communication devices are augmented to additionally include status information, such as position and/or conditions information. The conditions information can pertain to one or more of environmental conditions, device-related conditions, or user-related conditions. One or more status sensors associated with the communication devices can capture or obtain the status information. In the case of position information, the status sensor can be a receiver, such as a Global Positioning System (GPS) receiver or other means.

FIG. 1 is a block diagram of an enhanced messaging system 100 according to one embodiment of the invention. The enhanced messaging system 100 allows electronic messages (e.g., text messages) to be sent between mobile communication devices. The electronic messages being sent can be enhanced to include status information pertaining to (i) status of the associated mobile communication devices, (ii) status associated with the environment of the mobile communication devices, and/or (iii) status of the person(s) using the mobile communication device(s).

The enhanced messaging system 100 includes mobile communication devices 102, 104, 106 and 108. The mobile communication devices 102 and 104 communicate with a wireless network 110, and the mobile communication devices 106 and 108 communicate with a wireless network 112. The wireless networks 110 and 112 can be the same or different networks and can utilize same or different protocols. The wireless networks 110 and 112 can be coupled together and/or can couple to the Internet 114, and can support global messaging.

The enhanced messages are sent from one of the mobile communication devices to one or more other of the mobile communication devices. These enhanced messages can include additional information about the mobile communication device, its user and/or its environment. In one embodiment, the status information can include at least position (location) information and other status information. To provide the status information, the mobile communication devices 102, 104, 106 and 108 can include one or more status sensors, such as position detectors, and/or one or more other types of condition sensors for different conditions regarding the communication devices. A position detector

can provide position information pertaining to its corresponding mobile communication device. Similarly, a condition sensor provides condition information pertaining to conditions sensed at the corresponding mobile communication device. More particularly, the mobile communication device 102 includes a position detector 116 and at least one condition sensor 118; the mobile communication device 104 includes a position detector 120 and at least one condition sensor 122; the mobile communication device 106 includes a position detector 124 and at least one condition sensor 126; and the mobile communication device 108 includes a position detector 128 and at least one condition sensor 130.

In one embodiment, the position information is obtained from a global positioning system (GPS) receiver, which can be in a mobile communication device. In other words, the position detector can be a GPS receiver. The position information can be obtained or augmented by a local positioning system such as utilized with a local network (e.g., Bluetooth, Wi-Fi, etc.). The conditions information can vary with application. Examples of conditions that can be provided within the conditions information include environment conditions or conditions of the environment of the corresponding mobile communication device. Environment conditions include temperature, humidity, pressure, gaseous or liquid states, chemical compositions, wind speed, color composition, scent, light, sound, smoke, particle or radiation (e.g., infrared radiation). The conditions information can be pertaining to a mobile communication device itself, such as force or pressure asserted on it, or its vibration, acceleration, speed (velocity) or direction. The conditions information can also include user-related conditions. These are conditions related to the user, who is typically a living being and who may be using the corresponding mobile communication device. Examples of user-related conditions include the being's physical conditions (e.g., heart beat, temperature, pupil dilation, hunger, perspiration, tired or sick), volitional behavior (e.g., facial expressions, jumping or moving), or the user's emotional state, such as the user's mood. Examples of emotional states or moods include sad, happy, mad, stressed, or excited. Some of these conditions are not determined directly by sensors, but are instead determined indirectly through processing other sensor data.

In one embodiment, an enhanced messaging system can operate in a distributed manner with little or no centralized management for status information exchange. In other words, the exchange of status information can be peer-to-peer (e.g., from one mobile communication device to another) without an intermediate centralized server to store and manage distribution of the status information. Such an embodiment can operate without assistance from wireless networks service providers. The enhanced messaging system 100 shown in FIG. 1 is suitable for use as such an embodiment.

In another embodiment, an enhanced messaging system can operate in a centralized manner, such as shown below in FIG. 2. In the case of a centralized system, or at least one providing centralized assistance, the status information can be stored and/or processed by a separate entity, independent of the parties sending and receiving information.

FIG. 2 is a block diagram of an enhanced messaging system 200 according to one embodiment of the invention. The enhanced messaging system 200 provides web-based enhanced messaging between users of communication devices. The enhanced messages being sent from one of the communication devices to one or more other of the communication devices. These enhanced messages can include additional information pertaining to a communication

device, its user and/or its environment. In one embodiment, the status information can include at least position (location) information and conditions information.

According to the embodiment shown in FIG. 2, the enhanced messaging system 200 includes stationary communication devices 202 and 204. The enhanced messaging system 200 also includes mobile communication devices (MCD) 206 and 208. Typically, the mobile communication devices 206 and 208 are worn by, affixed to or carried by users. The enhanced messaging system 200 would normally be able to support multiple stationary communication devices, such as desktop computers, and mobile communication devices, such as mobile telephones, personal digital assistants and two-way pagers.

In general, messages can be transmitted (sent and/or received) between and/or among any of the communication devices, regardless of whether stationary or mobile. For discussion, it is assumed that a message is created and sent from the mobile communication device 206 to the stationary communication device 204. The message is assumed to be a text message, such as a real-time text message (e.g., instant message). In this example, the mobile communication device 206 acquires status information pertaining to the user, the device and/or the environment. The acquired status information is provided to the stationary communication device 204 along with the message.

The mobile communication devices 206 and 208 couple to a wireless network 210. The wireless network 210 couples to the Internet 212. Further, a status server 214 is coupled to the Internet 212. The status server 214 also couples to a status database 216. The Internet 212 can be replaced by other data networks (e.g., enterprise network, regional network, Local Area Network, Wide Area Network and global network).

The status information can include at least position (location) information and conditions information. The position information is obtained typically from a global positioning system (GPS) receiver within the first mobile communication device 206. The position information can be obtained or augmented by a local positioning system such as utilized with a local network (e.g., Bluetooth, Wi-Fi, etc.).

The conditions information can vary with application. Various examples of conditions that can be provided within the conditions information were noted above. The corresponding conditions sensor(s) can also be in the mobile communication device 206, or the sensor(s) can be wired or wirelessly coupled to the mobile communication device 206.

The status information that is obtained by the first mobile communication device 206 is sent by the first mobile communication device 206 to the status server 214 via the wireless network 210 and the Internet 212. The status server 214 stores the status information pertaining to the first mobile communication device 206 into the status database 216 such that it is associated with the first mobile communication device 206. The status server 214 monitors status information for numerous communication devices, including mobile communications devices and/or stationary communication device, and thus stores status information pertaining to numerous communication devices.

The enhanced messaging system 200 can also include at least one third-party 218. The third-party 218 is a user interested in status information acquired by mobile communication devices but does not normally receive the text messages also being sent.

The enhanced messaging system 200 can allow a recipient of the message to not only receive the text of the message but also the status information associated with the message. In

one embodiment, the recipient receives the status information with the message. The recipient of the message can, for example, include one or more of the mobile communication devices 206 and 208 or one or more of the stationary communication devices 202 and 204, or users thereof. In another embodiment, an authorized party, such as the user of the stationary communication devices 202 and 204 or the third-party 218, can interact with the status server 214 through a web interface so that such users are able to access certain status information via the status server 214 and the status database 216. The web interface can facilitate a user in accessing status information anytime anywhere.

FIG. 3 is a flow diagram of status message processing 300 according to one embodiment of the invention. The status message processing 300 is, for example, performed by a mobile communication device (e.g., mobile telephone, two-way pager) or other computing device (e.g., desktop computer, gateway, server).

Initially, the status message processing 300 receives 302 a message at a first mobile communication device. For example, a user of the mobile communication device would typically interact with the mobile communication device (e.g., through a user interface) to create the message. Hence, in this embodiment, the message is considered to be a user-entered message. The user-entered message can be a voice message, a text message, a video message or some other type of input, or some combination thereof. A text message is, for example, a standard email message, a short message (e.g., SMS message) or an instant message. Status information pertaining to the first mobile communication device (and/or its user or environment) can be acquired 304. As noted above, in one embodiment, the status information can include at least position (location) information and/or conditions information. Some or all of the status information can then be attached 306 to the user-entered message. In one embodiment, at least some of the status information has been processed before attachment. The processed status information is still considered as status information. With the status information attached 306 to the user-entered message, the user-entered message becomes an enhanced message. The enhanced message is then sent 308 from the first mobile communication device to another electronic device, such as a second mobile communication device (e.g., mobile telephone, personal digital assistant, or pager) or other computing device (e.g., portable or stationary computer). Typically, the sending of the enhanced message involves electronic transmission of the enhanced message over a wireless network as well as perhaps a wired network. Although the enhanced message is often sent from one mobile communication device to another mobile communication device, the message can alternatively be sent to another computing device, such as a personal computer coupled to the network. Following the operation 308, the status message processing 300 is complete and ends.

FIG. 4 is a flow diagram of send processing 400 according to one embodiment of the invention. The send processing 400 is, for example, performed by a mobile communication device or other computing device.

The send processing 400 initially produces 402 a message. In this embodiment, the message is a user-entered message such as a text message. The text message can, for example, be produced or initiated by a user of the mobile communication device or other computing device. However, in other embodiment, the message can be a voice message or a video message.

A decision 404 then determines whether status information is to be added to the text message. The decision 404

allows the user to limit or restrict the status information that is sent to others. For example, the user might restrict the status information such that it can only be sent to authorized persons or destinations. The restrictions can be imposed by a profile or configuration information associated with the user. In one implementation, a user can make use of a list of recipients permitted to receive status information (e.g., pre-authorized recipients). As another example, a dialog box (or other graphical user interface) could be displayed to allow the user to select none, some or all of the available status information to be sent generally with all text messages, or specifically with a particular text message. As still another example, default authorizations can control the status information that is to be sent to recipients. Yet, in another example, status information can have different levels. Some levels can be more confidential than others, or some levels can be more important than others. These levels can also be set by the user. Regardless, different recipients can receive different levels of status information.

In any case, when the decision 404 determines that status information is to be provided with the text message, the status information is acquired 406. The status information is acquired from the mobile communication device or other computing device that is sending the text message. For example, the status information can be acquired 406 from a position detector and at least one condition sensor within (wired or wirelessly coupled to) the mobile communication device.

Regardless of how or when acquired, the status information can then be embedded 408 in the text message. Once the status information has been embedded in 408 (or otherwise combined with or linked to) the text message, the resulting message is referred to as an enhanced message. The status information can be embedded in an open (e.g., as additional displayed information) or hidden manner (e.g., as undisplayed text). In one example, the status information is embedded in the text message using a markup language. The status information being embedded in the text message can also be encrypted, or the entire enhanced message can be encrypted. After the status information is embedded 408 (as well as directly after the decision 404 when no status information is to be added, the resulting message (regardless of whether enhanced or not) is sent 410 to a recipient. The recipient is typically a user of another mobile communication device or other computing device. However, the recipient can also be the another mobile communication device or other computing device. Following the operation 410, the send processing 400 is complete and ends.

FIG. 5 is a flow diagram of display processing 500 according to one embodiment of the invention. The display processing 500 is, for example, performed by a mobile communication device or other computing device. The display processing 500 is, for example, performed in response to a message being received due to the send processing 400 of FIG. 4. In other words, the display processing 500 can be performed by a computing device associated with a recipient that has received a message.

The display processing 500 begins with a decision 502 that determines whether a message has been received. When the decision 502 determines that a message has not yet been received, then the display processing 500 awaits the receipt of a message. On the other hand, when the decision 502 determines that a message has been received, a decision 504 then determines whether any status information is provided with the message that has been received. Here, the message is examined to determine whether status information is provided within the message. When the decision 504 deter-

mines that status information is provided with the message (and thus the message is an enhanced message), then the status information is extracted 506 from the message.

Next, the message as well as at least one representation of the status information are displayed 508. The representation (e.g., indication) of the status information being displayed can vary with implementation. In one embodiment, the representation is a graphical symbol that represents at least a portion of the status information. For example, a smiling face icon can represent a happy mood, a frown face icon can represent that the user is unhappy, etc. In another embodiment, the representation is textual information that is or represents a portion of the status information. In still another embodiment, the representation is a link (e.g., hyperlink) that provides access to at least a portion of the status information. For such representations, the status information can specify its presentation, or additional processing of the status information can determine an appropriate presentation.

The status information can also be interpreted, analyzed or processed before or while the representation to be displayed is determined. In one embodiment, such interpretation, analysis or processing can be performed, at least in part, by the device sending the message. As one example, the status information can include (or interpreted to include) temperature (e.g., ambient temperature) and user perspiration. Based on these two pieces of status information, one interpretation is that the user is perspiring (i.e., sweating) because of the high temperature.

As another example of the interpretation of status information, relative position of two computing devices can be computed and displayed. For example, if a receiving-computing device (either mobile or stationary) receives position information from a sending-computing device (preferably mobile), then the receiving-computing device (which knows its position) can determine and display the relative position (e.g., distance and/or direction) of the sending and the receiving-computing devices. Further, through use of other conditions information pertaining to the sending-computing device that might also be provided to the receiving-computing device, the receiving-computing device can also display the speed (velocity), direction of travel, etc. of the sending-computing device. Through additional interpretation or analysis of the conditions information, the speed (or average speed) could be used to categorize the type of movement of the sending-computing device, which would be available for display, as a symbol or other indication. As examples, the categories could be auto, bicycle, run, fast walk, slow walk, and stationary.

In yet another example, conditions information can include the user's mood. This can be measured in a number of different ways. One method is discussed in U.S. Pat. No. 5,774,591, entitled, "APPARATUS AND METHOD FOR RECOGNIZING FACIAL EXPRESSIONS AND FACIAL GESTURES IN A SEQUENCE OF IMAGES," which is hereby incorporated herein by reference. Such conditions information can be interpreted at the sending-computing device or the receiving-computing device. Conditions information can be a user's stress level. This piece of status information can, for example, be interpreted and transformed into a symbol, such as a stressed-face icon which the stress level is high. In one embodiment, both the raw data and the symbol(s) are transmitted to a receiving-computing device, but with only the symbol being displayed and the raw data being hidden. By selecting the displayed symbol or through other appropriate user-input, the receiving-computing device can additionally analyze or view the raw data.

Alternatively, when the decision **504** determines that status information is not provided with the message, then the message is displayed **510**. Here, there is no status information available to present; therefore, the message is simply displayed. Following the operations **508** and **510**, the display processing **500** is complete and ends.

The display processing **500** operates to present at least an indicator or representation of the status information through a display. In another embodiment, the status can be presented to the user of the mobile communication device or other computing device in other ways. For example, the status information could be presented by an audio output (e.g., synthesized voice), a tactile output or other types of outputs that can be sensed by the user, which is typically a living being, such as a human being.

In one aspect of the invention, status information can be automatically included with user-entered messages being sent as noted above. As another aspect of the invention, status information can be acquired and presented on request.

FIG. 6 is a flow diagram of status retrieval processing **600** according to one embodiment of the invention. The status retrieval processing **600** is, for example, performed by a mobile communication device or other computing device.

The status retrieval processing **600** begins with a decision **602** that determines whether a status request has been requested. The status request is provided by a requestor to acquire status information from another mobile communication device or other computing device. In one embodiment, the status request is initiated by a requestor. The requestor can be a user of the mobile communication device or other computing device. In another embodiment, the status request can be initiated by the mobile communication device or other computing device. When the decision **602** determines that a status request has not been requested, then the status retrieval processing **600** awaits such a request.

Once the decision **602** determines that a status request has been requested, a status request message is produced **604**. The status request message is then sent **606** from the requestor to a recipient. In one embodiment, the status request message is a short text message (e.g., SMS message) that need not be displayed at the recipient. A status request message that is not displayed at the recipient can be referred to as a dummy message. The recipient can be another mobile communication device or other computing device, or a user thereof.

Next, a decision **608** determines whether a status response message has been received by the requestor. The status response message includes status information associated with the recipient. The status response message is a message sent by the recipient in response to the status request message from the requestor. When the decision **608** determines that the status response message has not yet been received, then the status retrieval processing **600** awaits receipt of a status response message. On the other hand, when the decision **608** determines that a status response message (responsive to the status request message) has been received, then the status retrieval processing **600** continues. Namely, status information is extracted **610** from the status response message. Next, at least one representation of the status information is displayed **612**. The representation can vary with implementation. In one embodiment, the representation is a graphical symbol that represents at least a portion of the status information. In another embodiment, the representation is text that is or represents a portion of the status information. In another embodiment, the representation is a piece of video clip that is or represents a portion of the status information. In still another embodiment, the

representation is a link (e.g., hyperlink) that provides access to at least a portion of the status information. The status information can also be interpreted, analyzed or processed before or while the representation to be displayed is determined. Following the operation **600**, the status retrieval processing **600** is complete and ends.

FIG. 7 is a flow diagram of status request processing **700** according to one embodiment of the invention. The status request processing **700** is, for example, performed by a mobile communication device or other computing device. The status request processing **700** is, for example, performed in response to a status request message of the status retrieval processing **600** of FIG. 6.

The status request processing **700** begins with a decision **702** that determines whether a status request message has been received. When the decision **702** determines that a status request message has not yet been received, then the status request processing **700** awaits such a message. Once the decision **702** determines that a status request message has been received, status information for the associated mobile communication device or other computing device or user thereof is acquired **704**. A status response message is then produced **706** based on the status information. The status response message is then sent **708** to the requestor. The requestor can be considered to be a mobile communication device or other computing device, or a user thereof, that caused the status request message to be sent. According to one embodiment, once the status response message is sent **708**, the operations **610-612** of the status retrieval processing **600** of FIG. 6 can be performed.

As described above, status information is typically presented in some manner at the recipient (often presented concurrently with a message). In other embodiments, the status information can be stored in a database for later utilization. The messages can be subsequently searched, sorted or otherwise processed.

In still another aspect of the invention, status information can be automatically sent to one or more recipients whenever available or when changed. For example, one such embodiment could have a mobile communication device periodically or on events (e.g., status events) send its status information to another computing device. As another example, status information could be automatically sent to another computing device when changed by more than a threshold amount. This would enable the another computing device to maintain awareness of up-to-date status information of the mobile communication device. Like other embodiments, this embodiment can operate in a peer-to-peer manner or in a centralized manner.

Note that status sensors do not have to be embedded in a mobile communication device. A status sensor can be physically detached, but electronically coupled to a communication device through a wireless link, such as based on the Bluetooth or Wi-Fi technologies. In yet another embodiment, a status sensor electronically couples to a communication device through a wire connection.

In yet another embodiment, the sending of status information can be through user-activation. In other words, although a piece of status information is acquired via a status sensor, its transmission to another electronic device can depend on a user's voluntary action, such as pushing a button.

One application of the invention is to provide the status information with messages, such as text messages and in particular near real-time text messages, such as instant messages. Hence, users of computing devices, namely, mobile communication devices, can exchange near real-time

text messages and in doing so can also exchange status information. In some embodiments, the exchange of status information is achieved automatically, without user initiation.

The messages can be provided in a markup language format. The status information can be embedded or included in the messages also in a markup language. As examples, the markup language include HTML, HDML, WML, XML, etc. The messages and/or status information can also be provided in a programming language format, such as JAVA or C.

Another application of the invention is in the medical area. For example, a patient carries a mobile communication device with a position detector. He is also carrying one or more status sensors that can sense, for example, his body temperature, blood pressure, blood sugar or glucose level, blood oxygen, spirometry, ECG, heart rate, arrhythmias, brain wave, other sound wave measurable by a stethoscope, and/or body fat. The sensors can be non-invasive or invasive. Also, the sensor(s) can be coupled to the device in a wireless or wired manner. Such status information can be transmitted upon his command. In one embodiment, a patient's mobile communication device sends a message ("Very tired.") to an emergency clinic. It is an enhanced message that includes some of the patient's status information, such as his physical location and blood sugar level. In response, a specialist at the clinic sends one or more messages back, instructing the patient how to care for himself and/or controlling the release of insulin into the patient. In the mean time, the specialist can dispatch an ambulance to pick him up.

A number of embodiments have been described based on text messages. The present invention is also applicable to other types of messages, such as voice messages. In one embodiment, the message is provided with a voice call, and the mobile communication device is a mobile telephone (e.g., cell phone).

Also, a number of embodiments have been described regarding a device sending information to another device. In one embodiment, a device can broadcast enhanced messages to many devices.

In yet another embodiment, communication among devices can be monitored and charged by a third party. For example, the user of a communicating device can be billed depending on the amount of enhanced messages he has been sending or the amount or degree of enhancement to messages. In one embodiment, both the recipient and the sender of the enhanced messages are billed. In another embodiment, the more types of status messages included, the higher the bill. For example, enhanced messages with position, temperature and humidity information will cost more than enhanced messages with just position.

The various aspects can be used separately or in any combination.

The above-described system, methods and processes can be used together with other aspects of a monitoring system or mobile device, including the various aspects described in: (i) U.S. Provisional Patent Application No. 60/444,198, filed Jan. 30, 2003, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MONITORING, DELIVERING, MANAGING AND USING STATUS INFORMATION," which is hereby incorporated herein by reference; (ii) U.S. Provisional Patent Application No. 60/418,491, filed Oct. 15, 2002, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MONITORING, DELIVERING, MANAGING AND USING STATUS INFORMATION SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRE-

SENTING, MANAGING AND USING POSITION INFORMATION," which is hereby incorporated herein by reference; (iii) U.S. Provisional Patent Application No. 60/404,645, filed Aug. 19, 2002, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MONITORING, DELIVERING, MANAGING AND USING POSITION AND OTHER INFORMATION," which is hereby incorporated herein by reference; and (iv) U.S. Provisional Patent Application No. 60/375,998, filed Apr. 24, 2002, and entitled "SYSTEM, METHOD AND APPARATUS FOR ACQUIRING, PRESENTING, MANAGING AND USING POSITION INFORMATION," which is hereby incorporated herein by reference.

The invention can be implemented in software, hardware or a combination of hardware and software. The invention can also be embodied as computer readable code on a computer readable medium. The computer readable medium can be any data storage device that can store data which can thereafter be read by a computing device. Examples of the computer readable medium include read-only memory, random-access memory, CD-ROMs, magnetic tape, optical data storage devices, and carrier waves. The computer readable medium can also be distributed over network-coupled computer systems so that the computer readable code is stored and executed in a distributed fashion.

The advantages of the invention are numerous. Different embodiments or implementations may yield one or more of the following advantages. One advantage is that status information is able to be obtained easily while exchanging electronic messages or otherwise through use of electronic messages. Another advantage of the invention is that messages are able to be enhanced with status information acquired by sensors. Still another advantage of the invention is that it can operate in a point-to-point or centralized manner to gather and present status information between computing devices (e.g., mobile communication devices).

The many features and advantages of the present invention are apparent from the written description and, thus, it is intended by the appended claims to cover all such features and advantages of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation as illustrated and described. Hence, all suitable modifications and equivalents may be resorted to as falling within the scope of the invention.

What is claimed is:

1. A non-transitory computer readable medium including at least computer program code tangibly stored thereon for facilitating communication among users of mobile electronic devices, said computer readable medium comprising:
 computer program code for receiving message content for a text message via a first mobile electronic device;
 computer program code for accessing movement information regarding movement of the first mobile electronic device;
 computer program code for determining a plurality of other mobile electronic devices or users thereof that are authorized to receive the movement information;
 computer program code for determining whether at least one indication has been received from the first mobile electronic device to influence whether the movement information is to be provided with the text message, the at least one indication received being user-initiated via the first mobile electronic device and being for the text message;

15

computer program code for determining based at least in part on the at least one indication whether the movement information is to be provided with the text message, and

computer program code for initiating sending of the text message along with the movement information to each of the plurality of other mobile electronic devices via at least one wireless network, provided that the computer program code for determining determines that the movement information is to be provided with the text message, and provided that the computer program code for determining determines that the plurality of other mobile electronic devices or users thereof are authorized to receive the movement information.

2. A non-transitory computer readable medium including at least computer program code tangibly stored thereon for facilitating communication among users of mobile electronic devices, said computer readable medium comprising:

computer program code for receiving message content for an electronic message via a first mobile electronic device;

computer program code for accessing movement information regarding movement of the first mobile electronic device;

computer program code for determining a plurality of other mobile electronic devices or users thereof that are to receive the electronic message along with the movement information;

computer program code for determining whether at least one indication has been received from the first mobile electronic device to influence whether the movement information is to be provided with the electronic message, the at least one indication received being user-initiated via the first mobile electronic device and being for the electronic message;

computer program code for determining based at least in part on the at least one indication whether the movement information is to be provided with the electronic message, and

computer program code for initiating sending of the electronic message along with the movement information to each of the plurality of other mobile electronic devices via at least one wireless network, provided that the computer program code for determining determines that the movement information is to be provided with the electronic message, and provided that the computer program code for determining determines that the plurality of other mobile electronic devices or users thereof are to receive the electronic message along with the movement information.

3. A non-transitory computer readable medium including at least computer program code tangibly stored thereon for facilitating communication among users of mobile electronic devices, said computer readable medium comprising:

computer program code for receiving message content for an electronic message via a first mobile electronic device;

computer program code for accessing location information regarding location of the first mobile electronic device;

computer program code for determining a plurality of other mobile electronic devices or users thereof that are to receive the electronic message along with the location information;

computer program code for determining whether at least one indication has been received from the first mobile electronic device to influence whether the location

16

information is to be provided with the electronic message, the at least one indication received being user-initiated via the first mobile electronic device and being for the electronic message;

computer program code for determining based at least in part on the at least one indication whether the location information is to be provided with the electronic message, and

computer program code for initiating sending of the electronic message along with the location information to each of the plurality of other mobile electronic devices via at least one wireless network, provided that the computer program code for determining determines that the location information is to be provided with the electronic message, and provided that the computer program code for determining determines that the plurality of other mobile electronic devices or users thereof are to receive the electronic message along with the location information.

4. A non-transitory computer readable medium as recited in claim 3, wherein the message content comprises graphical content.

5. A non-transitory computer readable medium as recited in claim 3, wherein the message content comprises image data.

6. A non-transitory computer readable medium as recited in claim 5, wherein the electronic message is a SMS message.

7. A non-transitory computer readable medium as recited in claim 3, wherein the computer readable medium comprises:

computer program code for presenting the location information in a graphic manner.

8. A non-transitory computer readable medium as recited in claim 3, wherein the electronic message comprises a video message.

9. A non-transitory computer readable medium as recited in claim 3, wherein the message content comprises graphical content and text content.

10. A non-transitory computer readable medium as recited in claim 3, wherein the computer readable medium comprises:

computer program code for augmenting the electronic message to include the location information prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

11. A non-transitory computer readable medium as recited in claim 10, wherein said computer readable medium comprises:

computer program code for altering the location information acquired from the first mobile electronic device, prior to the computer program code for augmenting acting to augment the electronic message to include the location information.

12. A non-transitory computer readable medium as recited in claim 3, wherein said computer readable medium comprises:

computer program code for modifying the location information of the first mobile electronic device, prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

13. A non-transitory computer readable medium as recited in claim 12, wherein the computer program code for modifying the location information produces modified location

17

information that facilitates display of a graphical representation of the location information.

14. A non-transitory computer readable medium as recited in claim 13, wherein the computer readable medium comprises:

computer program code for embedding the modified location information in the electronic message prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

15. A non-transitory computer readable medium as recited in claim 14, wherein the message content comprises graphical content.

16. A non-transitory computer readable medium as recited in claim 15, wherein the electronic message is a SMS message.

17. A non-transitory computer readable medium as recited in claim 12, wherein the computer program code for modifying the location information produces modified location information based at least in part on a local network.

18. A non-transitory computer readable medium as recited in claim 17, wherein the local network comprises a Wi-Fi network.

19. A non-transitory computer readable medium as recited in claim 3, wherein the computer readable medium comprises:

computer program code for embedding the location information in the electronic message prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

20. A non-transitory computer readable medium as recited in claim 3, wherein the computer program code for accessing the location information is configured to determine the location information based on at least location data supplied by a GPS receiver provided in the first mobile electronic device.

21. A non-transitory computer readable medium as recited in claim 3, wherein the computer program code for accessing the location information is configured to determine the location information based on at least (i) location data supplied by a GPS receiver provided in the first mobile electronic device, and (ii) other location data associated with a local network available for use by the first mobile electronic device.

22. A non-transitory computer readable medium as recited in claim 3, wherein the location information regarding location of the first mobile electronic device is provided at least in part by a GPS receiver in the first mobile electronic device.

23. A non-transitory computer readable medium as recited in claim 3, wherein the location information regarding location of the first mobile electronic device is provided at least in part by a local positioning system.

24. A non-transitory computer readable medium as recited in claim 3, wherein the location information regarding location of the first mobile electronic device is provided at least in part by a position detector in the first mobile electronic device.

25. A non-transitory computer readable medium as recited in claim 3, wherein said computer readable medium comprises:

computer program code for processing the location information to determine a location designation of the first mobile electronic device; and

computer program code for embedding the location designation in the electronic message, prior to the com-

18

puter program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

26. A non-transitory computer readable medium as recited in claim 3, wherein said computer readable medium comprises:

computer program code for receiving a message from another mobile electronic device via the at least one wireless network;

computer program code for determining whether the received message includes at least received status information;

computer program code for extracting the status information from the received message from the another mobile electronic device when the computer program code for determining determines that the received message includes at least the received status information; and

computer program code for displaying at least a portion of the received message and at least one representation of the extracted status information when the computer program code for determining determines that the received message includes at least the received status information.

27. A non-transitory computer readable medium as recited in claim 26, wherein the received status information includes at least location information associated with the another mobile electronic device, and wherein the at least one representation of the extracted status information being displayed displays a representation of the location information associated with the another mobile electronic device.

28. A non-transitory computer readable medium as recited in claim 26, wherein the received status information includes at least movement information associated with the another mobile electronic device, and wherein the at least one representation of the extracted status information being displayed displays a visual representation of the movement information associated with the another mobile electronic device.

29. A non-transitory computer readable medium as recited in claim 3, wherein the computer program code for receiving message content for the electronic message comprises computer program code for presenting a user interface to enable the message content to be received.

30. A non-transitory computer readable medium as recited in claim 3, wherein the computer program code for determining the plurality of other mobile electronic devices or users thereof that are to receive the electronic message along with the location information comprises computer program code for presenting a graphical user interface to enable a user of the first mobile electronic device to designate the plurality of other mobile electronic devices or users thereof that are to receive the electronic message along with the location information.

31. A non-transitory computer readable medium as recited in claim 30, wherein the computer program code for presenting the graphical user interface to enable a user of the first mobile electronic device to designate the plurality of other mobile electronic devices or users thereof that are to receive the the electronic message along with the location information comprises computer program code for displaying a list of potential recipients.

32. A non-transitory computer readable medium as recited in claim 30, wherein said computer readable medium comprises:

computer program code for processing the location information to determine a location designation of the first mobile electronic device;

computer program code for embedding the location designation in the electronic message, prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices;

computer program code for receiving a message from another mobile electronic device via the at least one wireless network;

computer program code for determining whether the received message includes at least received status information;

computer program code for extracting the status information from the received message from the another mobile electronic device when the computer program code for determining determines that the received message includes at least the received status information; and

computer program code for displaying at least a portion of the received message and at least one representation of the extracted status information when the computer program code for determining determines that the received message includes at least the received status information,

wherein the message content comprises graphical content.

33. A non-transitory computer readable medium as recited in claim **32**, wherein the electronic message is a SMS message.

34. A non-transitory computer readable medium as recited in claim **3**, wherein the first mobile electronic device is a mobile communication device.

35. A non-transitory computer readable medium as recited in claim **3**, wherein the first mobile electronic device is a mobile telephone.

36. A non-transitory computer readable medium as recited in claim **2**, wherein the computer readable medium comprises:

computer program code for presenting the movement information in a graphic manner.

37. A non-transitory computer readable medium as recited in claim **2**, wherein the movement information comprises a speed of the first mobile electronic device.

38. A non-transitory computer readable medium as recited in claim **37**, wherein said computer readable medium comprises:

computer program code for initiating display of a graphical indication of the speed.

39. A non-transitory computer readable medium as recited in claim **37** wherein the movement information of the first mobile electronic device is provided at least in part by a sensor within the first mobile electronic device.

40. A non-transitory computer readable medium as recited in claim **2**, wherein said computer readable medium comprises:

computer program code for processing the movement information to determine speed of the first mobile electronic device.

41. A non-transitory computer readable medium as recited in claim **40**, wherein said computer readable medium comprises:

computer program code for initiating display of a graphical indication of the speed.

42. A non-transitory computer readable medium as recited in claim **2**, wherein the computer program code for accessing the movement information is configured to determine the

movement information based on at least movement data supplied by a sensor in the first mobile electronic device.

43. A non-transitory computer readable medium as recited in claim **2**, wherein said computer readable medium comprises:

computer program code for receiving a user input from the first mobile electronic device via a user interface displayed at the first mobile electronic device, wherein the user input via the user interface influences whether the movement information is provided with the electronic message.

44. A non-transitory computer readable medium as recited in claim **2**, wherein said computer readable medium comprises:

computer program code for processing the movement information to determine a movement designation for the first mobile electronic device; and

computer program code for embedding the movement designation in the electronic message prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

45. A non-transitory computer readable medium as recited in claim **2**, wherein said computer readable medium comprises:

computer program code for modifying the movement information of the first mobile electronic device prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

46. A non-transitory computer readable medium as recited in claim **45**, wherein the computer program code for modifying the movement information produces modified movement information that facilitates display of a graphical representation of the movement information.

47. A non-transitory computer readable medium as recited in claim **46**, wherein the computer readable medium comprises:

computer program code for embedding the modified movement information in the electronic message prior to the computer program code for initiating sending acting to initiate sending such to the plurality of other mobile electronic devices.

48. A non-transitory computer readable medium as recited in claim **47**, wherein the message content comprises graphical content.

49. A non-transitory computer readable medium as recited in claim **48**, wherein the electronic message is a SMS message.

50. A non-transitory computer readable medium as recited in claim **2**, wherein said computer readable medium comprises:

computer program code for receiving a message from another mobile electronic device via the at least one wireless network;

computer program code for determining whether the received message includes at least received status information;

computer program code for extracting the status information from the received message from the another mobile electronic device when the computer program code for determining determines that the received message includes at least the received status information; and

computer program code for displaying at least a portion of the received message and at least one representation of the extracted status information when the computer

program code for determining determines that the received message includes at least the received status information.

51. A non-transitory computer readable medium as recited in claim **50**, wherein the received status information includes at least location information associated with the another mobile electronic device, and wherein the at least one representation of the extracted status information being displayed displays a representation of the location information. 5 10

52. A non-transitory computer readable medium as recited in claim **50**, wherein the received status information includes at least movement information associated with the another mobile electronic device, and wherein the at least one representation of the extracted status information being displayed displays a visual representation of the movement information. 15

53. A non-transitory computer readable medium as recited in claim **2**, wherein the computer program code for receiving message content for the electronic message comprises computer program code for presenting a user interface to enable the message content to be received. 20

* * * * *